

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/15/2014 Version: 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Product name : Ammonium Acetate Buffer for Iron

Product code : LC10970 Formula : APHA 3500-Fe B

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For laboratory and manufacturing use only.

# 1.3. Details of the supplier of the safety data sheet

LabChem Inc

Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court

Zelienople, PA 16063 - USA T 412-826-5230 - F 724-473-0647 info@labchem.com - www.labchem.com

# 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### **GHS-US** classification

Skin Corr. 1B H314 Eye Dam. 1 H318 STOT SE 3 H335 Aquatic Acute 3 H402

# 2.2. Label elements

# **GHS-US** labelling

Hazard pictograms (GHS-US)





GHS05 GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

H402 - Harmful to aquatic life

Precautionary statements (GHS-US) : P260 - Do not breathe vapours, mist, spray

P264 - Wash exposed skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P363 - Wash contaminated clothing before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container to comply with local, state and federal regulations

# 2.3. Other hazards

Other hazards not contributing to the : None under normal conditions

07/15/2014 EN (English) Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

classification

### 2.4. Unknown acute toxicity (GHS-US)

No data available

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Acetic Acid	(CAS No) 64-19-7	68.75	Flam. Liq. 3, H226 Skin Corr. 1B, H314 Eye Dam. 1, H318
Ammonium Acetate	(CAS No) 631-61-8	22.36	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 3, H402
Water	(CAS No) 7732-18-5	8.89	Not classified

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a

POISON CENTER or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a POISON CENTER or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or

doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Nausea. Vomiting. Diarrhoea.

Chronic symptoms : Cracking of the skin. Coughing. Inflammation/damage of the eye tissue.

# 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Reactivity : Thermal decomposition generates : Corrosive vapours.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

# 6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.

Emergency procedures : Evacuate unnecessary personnel.

07/15/2014 EN (English) 2/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

# 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of

vapour. Do not breathe dust, mist. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash ... thoroughly after handling. Wash contaminated clothing before reuse.

# 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources.,

Ignition sources, incompatible materials, metals. Keep container tightly closed.

Incompatible products : Strong oxidizers. Strong bases.
Incompatible materials : Sources of ignition. Direct sunlight.

#### 7.3. Specific end use(s)

No additional information available

### **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Acetic Acid (64-19-7)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	10 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	25 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity

of any potential exposure. Ensure adequate ventilation.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or face shield. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Colourless

Odour : characteristic

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point : No data available

Freezing point : No data available

07/15/2014 EN (English) 3/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point : No data available Flash point : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapour pressure : No data available Relative vapour density at 20 °C : No data available Relative density : No data available

Solubility : Water: Solubility in water of component(s) of the mixture :

Acetic Acid: Complete

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

#### 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Thermal decomposition generates: Corrosive vapours.

#### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Not established.

# 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapours. Gaseous ammonia.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity : Not classified

Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000.00000000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated : Not classified

exposure)

07/15/2014 EN (English) 4/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard : Not classified

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Nausea. Vomiting. Diarrhoea.

Chronic symptoms : Cracking of the skin. Coughing. Inflammation/damage of the eye tissue.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecology - water : Harmful to aquatic life.

Ammonium Acetate (631-61-8)	
LC50 fishes 1	1.06 mg/l
LC50 other aquatic organisms 1	238 mg/l

Acetic Acid (64-19-7)	
LC50 fishes 1	75 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 1	47 mg/l (24 h; Daphnia magna; Not neutralized)
EC50 other aquatic organisms 1	> 5000 mg/l (5 h; Activated sludge)
LC50 fish 2	94 mg/l (96 h; Oryzias latipes)
EC50 Daphnia 2	95 mg/l (24 h; Daphnia magna; Static system)
TLM fish 1	100 ppm (96 h; Carassius auratus)
Threshold limit algae 1	90 mg/l (192 h; Microcystis aeruginosa; Neutralized)
Threshold limit algae 2	4000 mg/l (192 h; Scenedesmus quadricauda; Neutralized)

# 12.2. Persistence and degradability

Ammonium Acetete (C24 C4 C)

Ammonium Acetate Buffer for Iron	
Persistence and degradability	Not established.
Persistence and degradability	Not established.

Ammonium Acetate (631-61-6)		
Persistence and degradability	Not established.	

Acetic Acid (64-19-7)		
Persistence and degradability	Readily biodegradable in water. Inherently biodegradable. Biodegradable in the soil.	
Biochemical oxygen demand (BOD)	0.6 - 0.74 g O □/g substance	
Chemical oxygen demand (COD)	1.03 g O□/g substance	
ThOD	1.07 g O□/g substance	
BOD (% of ThOD)	0.56 - 0.69 % ThOD	

Water (7732-18-5)	
Persistence and degradability	Not established.

# 12.3. Bioaccumulative potential Ammonium Acetate Buffer for Iron

Bioaccumulative potential	Not established.
Ammonium Acetate (631-61-8)	
Log Pow	-2.79
Bioaccumulative potential	Not established.
Acetic Acid (64-19-7)	

Acetic Acid (64-19-7)	
Log Pow	-0.31 (Experimental value)
Bioaccumulative potential	Bioaccumulation: not applicable.

Water (7732-18-5)	
Bioaccumulative potential	Not established.

# 12.4. Mobility in soil

07/15/2014 EN (English) 5/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetic Acid (64-19-7)	
Surface tension	0.028 N/m (20 °C)

Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming No known ecological damage caused by this product.

Other information : Avoid release to the environment.

# **SECTION 13: Disposal considerations**

#### Waste treatment methods

: Dispose in a safe manner in accordance with local/national regulations. Dispose of Waste disposal recommendations

contents/container to comply with local, state and federal regulations.

Ecology - waste materials : Avoid release to the environment.

# **SECTION 14: Transport information**

In accordance with DOT

Transport document description : UN2790 Acetic acid solution not less than 50 percent but not more than 80 percent acid, by

mass, 8, II

UN-No.(DOT) : 2790 DOT NA no. : UN2790

**DOT Proper Shipping Name** Acetic acid solution

not less than 50 percent but not more than 80 percent acid, by mass

: 8 - Class 8 - Corrosive material 49 CFR 173.136

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT)

: 8 - Corrosive



Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102)

A3 - For combination packagings, if glass inner packagings (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packagings.

A6 - For combination packagings, if plastic inner packagings are used, they must be packed in tightly closed metal receptacles before packing in outer packagings.

A7 - Steel packagings must be corrosion-resistant or have protection against corrosion.

A10 - When aluminum or aluminum alloy construction materials are used, they must be resistant to corrosion.

B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) 154 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242 DOT Quantity Limitations Passenger aircraft/rail : 1 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

07/15/2014 EN (English) 6/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

**Additional information** 

Other information : No supplementary information available.

**ADR** 

Transport document description

Transport by sea

No additional information available

Air transport

No additional information available

# **SECTION 15: Regulatory information**

# 15.1. US Federal regulations

Ammonium Acetate Buffer for Iron	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Ammonium Acetate (631-61-8)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

Acetic Acid (64-19-7)	
Not listed on the United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists):	5000 lb

# 15.2. International regulations

### **CANADA**

	Ammonium Acetate Buffer for Iron	
	WHMIS Classification	Class E - Corrosive Material
Ammonium Acetate (631-61-8)		
Animonium Acetate (03-191-0)		12.0

Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Acetic Acid (64-19-7)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class E - Corrosive Material

Water (7732-18-5)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

# **EU-Regulations**

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

### 15.2.2. National regulations

Acetic Acid (64-19-7)
Listed on the Canadian IDL (Ingredient Disclosure List)

07/15/2014 EN (English) 7/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

# **SECTION 16: Other information**

:

Other information : None.

Full text of H-phrases: see section 16:

Aquatic Acute 3	Hazardous to the aquatic environment — Acute Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H402	Harmful to aquatic life

NFPA health hazard : 3 - Short exposure could cause serious temporary or


 $\underset{\cdot}{\text{residual injury even though prompt medical attention was}}$ 

given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



### **HMIS III Rating**

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 1 Slight Hazard
Physical : 0 Minimal Hazard

Personal Protection : H

SDS US (GHS HazCom 2012)

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.

07/15/2014 EN (English) 8/8